

The Original **TUFFTRUCKBAG**

READ THIS FIRST!

WARRANTY INFORMATION

Please Read Carefully

The Tuff Truck Bag has a 90 DAY PRODUCT WARRANTY issued from the day of purchase. The warranty is a standard manufacturer warranty that covers possible basic faults or defects of the bag.

This warranty DOES cover:

1. Bag seams coming undone.
2. Zipper breaking, not closing completely. (zipper teeth)
3. Corner rings: metal breaking, fabric tearing or coming undone (not PVC Waterproof Material - SEE BELOW)

For more info on returns NOT covered by the product warranty please see the Returns section on our website: www.TuffTruckBag.com.

This warranty DOES NOT cover:

1. Burn holes created in the bag.
2. Cuts, slices or holes poked through the bag.
3. Man-made damage to the bag.
4. Damage to the (included) tote bag, or 4 adjustable bungee cords.
5. Loose velcro, velcro strips falling off.
6. Too much tension causing the corner rings to rip off (DO NOT SET TOO MUCH STRAP TENSION - SEE BELOW).



VERY IMPORTANT Corner Ring Information

- Too much tension WILL POSSIBLY TEAR OFF THE CORNER RINGS - this is NOT COVERED by the manufacturer warranty! Do not set your adjustable straps with too much cord tension, tension is up to user so it cannot be covered.
- MAKE SURE that the bag sits comfortably ON THE BED OF THE TRUCK to ease tension on corner rings.
- There are 8 corner rings, but ONLY 4 ARE NEEDED TO SECURE THE BAG in place. PLEASE NOTE that bag setup DOES NOT REQUIRE the use of all 8 corner rings. 8 rings are only in place in case bag needs to sit in a different position such as on its side, etc...

TUFF TRUCK BAG SETUP INSTRUCTIONS

Bag Setup Step-By-Step



1: Roll bag out fully, laying flat with the Tuff Truck Bag logo facing up.



2: Loosely connect adjustable bungee straps to truck bed, and top 4 corner rings (there are 8 total rings, but only 4 are needed to setup the bag).




3: Load bag with cargo, luggage, etc... Once bag is loaded close main zipper and adjust straps TO USER PREFERENCE.


IMPORTANT NOTE:

Straps do not require much tension! Weight of cargo will keep the bag in place, the straps secure the bag from wind, or sliding during travel. Important to note that straps and corner tension is set by USER and CAN NOT be under warranty because of this. Corners are secure and heavy duty, but minimal strap settings will work fine to fasten the bag in place.

Hook & Strap Setup: Step-By-Step



1: Connect strap hooks to bag corner and to truck bed. Slide hook end through bag corner.



2: Pull hook up through the bag's corner ring and loop cord into the small back hook.



3: Loop larger hook around cord as shown above. Cord strap should stay in place, but still loose as to not place too much tension on rings.



4: Proceed the same way for all 4 corner rings. All straps should be secure, but not too tight as to place too much tension on bags' corners.



IMPORTANT

- DO NOT GET INSIDE BAG, OR ENCLOSED BAG. Air can be limited inside of enclosed bag space.
- There are 8 Total corner rings, BUT YOU ONLY NEED TO USE 4 corner rings to secure the bag in place.